



淨冷型

室內機 (Wall Mounted Indoor)



1匹 MC09MI



1.5匹 MC12MI



2匹 MC18MI



2.5匹 MC24MI

室外機 (R32 Cool Only Multi Outdoor)



18K Capacity range
MC18MO



24K Capacity range
MC24MO



27K Capacity range
MC27MO



36K Capacity range
MC36MO



42K Capacity range
MC42MO

室外機	室內機										
18K One Drive Two MC18MO	One unit	12	18								
	Two units	9+9	9+12	9+18	12+12	12+18					
24K One Drive Three MC24MO	One unit	12	18	24							
	Two units	9+9	9+12	9+18	12+12	12+18					
	Three units	9+9+9									
27K One Drive Three MC27MO	One unit	18	24								
	Two units	9+9	9+12	9+18	12+12	12+18					
	Three units	9+9+9	9+9+12	9+9+18	9+12+12	12+12+12					
36K One Drive Four MC36MO	One unit	/									
	Two units	9+9	9+12	9+18	9+24	12+12	12+18	12+24			
	Three units	9+9+9	9+9+12	9+9+18	9+9+24	9+12+12	9+12+18	9+12+24	12+12+12	12+12+18	12+12+24
	Four units	9+9+9+9	9+9+9+12	9+9+9+18	9+9+12+12	9+9+12+18	9+12+12+12	12+12+12+12			
42K One Drive Five MC42MO	One unit	/									
	Two units	9+12	9+18	9+24	12+12	12+18	12+24				
	Three units	9+9+9	9+9+12	9+9+18	9+9+24	9+12+12	9+12+18	9+12+24	12+12+12	12+12+18	12+12+24
	Four units	9+9+9+9	9+9+9+12	9+9+9+18	9+9+9+24	9+9+12+12	9+9+12+18	9+9+12+24			
		9+12+12+12	9+12+12+18	9+12+12+24	12+12+12+12	12+12+12+18	12+12+12+24				
	Five units	9+9+9+9+9	9+9+9+9+12	9+9+9+9+18	9+9+9+9+24	9+9+9+12+12	9+9+9+12+18	9+9+9+12+24	9+9+12+12+12		

一部室外機可連接多部室內機

規格表

室內機		淨冷型			
型號 Model		MC09MI	MC12MI	MC18MI	MC24MI
冷凍能力 Cooling Capacity	千瓦(BTU/小時) kW(BTU/h)	2.6 (9,000)	3.5 (12,000)	5.3 (18,000)	7.0 (24,000)
尺寸(闊x高x深) Dimensions(WxHxD)	毫米 mm	795x295x225	795x295x225	957x302x213	1040x327x220
冷媒配管直徑(毫米mm/吋inch) Refrigerant Piping Diameter	液體Liquid 氣體Gas	6.35mm(1/4in) 9.52mm(3/8in)	6.35mm(1/4in) 12.7mm(1/2in)	9.52mm(3/8in) 15.9mm(5/8in)	

室外機		淨冷型				
型號 Model		MC18MO	MC24MO	MC27MO	MC36MO	MC42MO
冷凍能力-額外(最小-最大) Cooling Capacity-Rated(Min-Max)	千瓦 kW	5.28 (2.28~5.72)	7.03 (2.11~8.44)	7.91 (3.18~8.21)	10.55 (3.64~10.84)	12.31 (3.02~12.31)
	BTU/小時 BTU/h	18000 (7800~19500)	24000 (7200~28800)	27000 (10850~28000)	36000 (12430~37000)	42000 (10300~42000)
耗電量(冷凍)-額外(量小-量大) Power Consumption(Cooling)-Rated(Min-Max)	千瓦 kW	1635 (690~2000)	2125 (319~3350)	2450 (290~3100)	3300 (330~4250)	3810 (280~4650)
尺寸(闊x高x深)毫米 Dimensions(WxHxD) mm	室內 室外	805x554x330	890x673x342	890x673x342	946x810x410	946x810x410
冷媒配管直徑(毫米mm/吋inch) Refrigerant Piping Diameter	液體Liquid 氣體Gas	2x6.35mm(2x1/4in) 2x9.52mm(2x3/8in)	4x6.35mm(4x1/4in) 4x9.52mm(4x3/8in)	3x6.35mm(3x1/4in) 3x9.52mm(3x3/8in)	4x6.35mm(4x1/4in) 3x9.52mm(3x1/2in)	5x6.35mm(5x1/4in) 4x9.52mm(4x1/2in)
供電來源 Source of Power Supply	室外機					
插頭 Plug Type	不連插頭					

產品特點



ion PLUS高濃度正負離子 主動殺菌

持續釋放正負離子，濃度達 4.6×10^6 / 立方厘米[△]，淨化空氣。



手機 Wifi 遙控器

下載手機應用程式，隨時隨地啟動冷氣機、調校操作模式及溫度。自訂睡眠溫度曲線，調校每小時的溫度，有效避免室溫過低而著涼。



四合一冷觸媒活性碳銀離子 抗菌過濾網

有效消除異味達95.5%[◎]，減少甲醛達98%[◎]，淨化空氣；高效消除致病細菌—金葡萄球菌、大腸桿菌、鼠傷寒沙門氏菌，抗菌達99%[◆]。



「隨處走」調節溫度

智能遙控器偵測周圍的溫度，當室內溫度高於預設溫度時，冷氣機自動提升製冷效能，為家居調節最舒適的室溫。

其他功能



3D DC Inverter



獨立抽濕



ECO Sleep
省電模式



High Power
急速模式



Silence
寧靜模式



Self Clean
機內防霉



導風葉
角度記憶



1年全機及
1年壓縮機保用



無線遙控器

△根據 Zhenjieng Hanbang Technology Co., Ltd 測試，報告編號: ZJHBKJ-2005004

◎根據 China National Analytical Center, Guangzhou 測試，報告編號: 2012007586b及2014006460b

◆根據 Guangdong Detection Center of Microbiology 測試，報告編號: 2012FM2285

美佳冷氣(香港)有限公司
MECAN AIRCONDITIONING (HONG KONG) LIMITED

香港灣仔沙咀道381-389號榮亞工業大廈.24樓D室
FLAT D, 24/F, YOUNG YA INDUSTRIAL BUILDING,
381-389 SHA TSUI ROAD, TSUEN WAN, HK

傳真/Fax: (852)31084689

網站/Website: www.mecanhk.com
客戶服務熱線/Customer Service Hotline:
(852)21163469